

Fiberglass Stabantenne Technical Data – CTX3633A

Multiband Antenna für 2G-3G-4G-5G und WiFi Frequenzen

Model CTX3633A - Specifications	
Antenna Type	End-fed 1/2 λ coaxial MULTI band dipole antenna High quality UHF antenna for professional use <ul style="list-style-type: none"> • Full omni-directional radiation pattern • NO GROUNDPLANE NEEDED
Frequency	698-960 / 1427-1518 / 1710-2170 / 2300-2690 / 3300-3800 MHz
Bands	5G: 700/800/900/1500/1800/2100/2600/3500 MHz 4G: 700/800/1800/1900/2600 MHz 3G: 700/800/900/2100 MHz 2G: 850/900/1800/1900 MHz WiFi: 2.4 GHz
Impedance	Nom. 50 Ω
Polarisation	Vertical
Gain	2.15dBi (698-960 MHz) 5.15dBi (1427-1518 / 1710-2170 MHz) 9.15dBi (2300-2690 / 3300 – 3800 MHz)
Bandwidth	See Frequency
VSWR	698-960 MHz < 3.0 1427-2690 MHz..... < 2.5 3300-3800 MHz..... < 2.5
max. Power	100 Watt
Colour	White and chrome
Length (whip)	Approx. 465 mm
Weight	Approx. 0,5 kg
Mounting	On 1" threaded pole with Revolving Nut Kit or on optionally brackets
Material	UV Protected PC, PTFE, PE and chromed solid brass
Temperature	-55°C - +70°C
Connector	N (f)
Protection Class	IP66 Classified (Outdoor capable)

